



GTP International, LTD

"Results Delivered"

Product Specification Sheet

Series Name: FreeFit

Product Type: LVT

Standard Product Specifications:

Size:	6" x 36", 6" x 48", 18" x 18", 12" x 24"
Overall Thickness:	4mm
Wear layer Thickness:	20mil (.5mm)
Construction:	Layered plank consisting of UV coating, wear layer, design film, and backing
Edge:	Square
Standard Colors:	60+ colors, Custom colors available
Installation Method:	Loose Lay, Perimeter adhered, Full spread glued
Limited Wear Warranty:	15 Year Commercial, Limited Lifetime Residential
Embossing Textures:	Smooth, Wood Grain, Hand Scraped Wood, Slate, Travertine/ Stone Tile

Packaging Specs:

Square Ft/ Box:	27 (18" x 18" and 6" x 36")/ 28 (6" x 48" and 12" x 24")
Boxes/ Pallet:	40 (18" x 18")/ 42 (6" x 36")/ 48 (6" x 48" and 12" x 24")
Pallets/ Container:	20
Square Ft/ Container	21,600 (18" x 18")/ 22,680 (6" x 36")/ 26,880 (6" x 48" and 12" x 24")

Product Testing:

Characteristic	Test Method	Result
Static Load Limit	ASTM F-970	Pass
Residual Indentation	ASTM F-1914	Pass
Static Coefficient of Friction	ASTM C-1028	0.6 Wet and Dry
Abrasion Resistance	ASTM D-3884	Pass
Critical Radiant Flux	ASTM E-648	Class 1
Specific Optical Density	ASTM E-662	Pass
Thickness	ASTM F-386	Pass
Squareness	ASTM F-2055	Pass
Flexibility	ASTM F-137	Pass
Dimensional Stability	ASTM F-2199	Pass
Chemical Resistance	ASTM F-925	Pass
Resistance to Heat	ASTM F-1514	Pass
Resistance to Light	ASTM F-1515	Pass
Lead and Heavy Metal Content	ASTM F-963	Pass
IIC (Impact Insulation Class)*	ASTM E-989/ ASTM E-492	37
STC (Sound Transmission Class)*	ASTM E-90/ ASTM E-413	51

*Tested over 6" Concrete Slab with Drop-Ceiling Assembly